

JAPAN SPECIFIED RADIO EQUIPMENT

TEST REPORT

For

WiFi+Bluetooth 5.2 System on Module

Trade Name: TechNexion

Model: PIXI-IW416

Issued to

TechNexion Ltd.

16F-5, No. 736, Zhongzheng Road, ZhongHe District, 23511, New Taipei City, Taiwan

Issued by

Compliance Certification Services Inc.

Wugu Laboratory

No.11, Wugong 6th Rd., Wugu Dist.,

New Taipei City, Taiwan

Issued Date: August 7, 2023

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMWK2305001503KR

Page 2 / 193
Rev. 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	August 7, 2023	Initial Issue	ALL	Allison Chen

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	6
2. SUMMARY OF TEST RESULTS	8
2.1 WLAN IEEE 802.11B (CH1~CH13).....	8
2.2 WLAN IEEE 802.11G (CH1~CH13)	9
2.4 WLAN IEEE 802.11N HT20 (CH1~CH13).....	10
2.5 WLAN IEEE 802.11N HT40 (CH3~CH11).....	11
2.6 BLUETOOTH (CH0~CH78) (FOR GFSK).....	12
2.7 BLUETOOTH (CH0~CH78) (FOR $\pi/4$ DQPSK)	13
2.8 BLUETOOTH (CH0~CH78) (FOR 8DPSK).....	14
2.9 BLE 1M (CH0~CH39) (FOR GFSK).....	15
2.10 BLE 2M (CH0~CH39) (FOR GFSK).....	16
3. EUT DESCRIPTION	17
4. TEST METHODOLOGY & CONDITIONS	19
4.1 TEST CONDITIONS.....	19
4.2 DESCRIPTION OF TEST MODES	23
4.3 TESTING APPLIED STARDARDS.....	23
4.4 RF SHIELDING METHOD.....	24
4.5 SETUP OF EQUIPMENT UNDER TEST	24
5. INSTRUMENT AND CALIBRATION	25
5.1 MEASURING INSTRUMENT CALIBRATION	25
5.2 TEST AND MEASUREMENT EQUIPMENT	25
5.3 MEASUREMENT UNCERTAINTY	26
6. TEST RESULT FOR IEEE 802.11B (CH1~CH13)	27
6.1 FREQUENCY ERROR.....	27
6.2 RF OUTPUT POWER	29
6.3 UNWANTED EMISSION STRENGTH	31
6.4 OCCUPIED BANDWIDTH (99%).....	40
6.5 SPREAD-SPECTRUM BANDWIDTH (90%).....	43
6.6 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER	46
7. TEST RESULT FOR IEEE 802.11G (CH1~CH13)	52
7.1 FREQUENCY ERROR.....	52
7.2 RF OUTPUT POWER	54
7.3 UNWANTED EMISSION STRENGTH	56
7.4 OCCUPIED BANDWIDTH (99%).....	65
7.5 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER	68
8. TEST RESULT FOR IEEE 802.11N HT20 (CH1~CH13)	74
8.1 FREQUENCY ERROR.....	74
8.2 RF OUTPUT POWER	76
8.3 UNWANTED EMISSION STRENGTH	78
8.4 OCCUPIED BANDWIDTH (99%).....	87
8.5 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER	90

Report No.: TMWK2305001503KR

9. TEST RESULT FOR IEEE 802.11N HT40 (CH3~CH11)	96
9.1 FREQUENCY ERROR	96
9.2 RF OUTPUT POWER	98
9.3 UNWANTED EMISSION STRENGTH	100
9.4 OCCUPIED BANDWIDTH (99%)	109
9.5 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER	112
9.6 CARRIER SENSE CAPABILITY	118
10. TEST RESULT FOR BLUETOOTH (CH0~CH78) (FOR GFSK)	119
10.1 FREQUENCY ERROR	119
10.2 ANTENNA POWER	121
10.3 UNWANTED EMISSION STRENGTH	122
10.4 OCCUPIED BANDWIDTH –NORMAL (99%).....	125
10.5 SPREAD-SPECTRUM BANDWIDTH –NORMAL (90%)	126
10.6 OCCUPIED BANDWIDTH –AFH-(99%)	127
10.7 SPREAD-SPECTRUM BANDWIDTH –AFH(90%)	128
10.8 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER	129
10.9 DWELL TIME	131
11. TEST RESULT FOR BLUETOOTH (CH0~CH78) (FOR $\pi/4$DQPSK)	132
11.1 FREQUENCY ERROR	132
11.2 ANTENNA POWER	134
11.3 UNWANTED EMISSION STRENGTH	135
11.4 OCCUPIED BANDWIDTH –NORMAL (99%).....	138
11.5 SPREAD-SPECTRUM BANDWIDTH –NORMAL (90%)	139
11.6 OCCUPIED BANDWIDTH –AFH-(99%)	140
11.7 SPREAD-SPECTRUM BANDWIDTH –AFH(90%)	141
11.8 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER	142
11.9 DWELL TIME	144
12. TEST RESULT FOR BLUETOOTH (CH0~CH78) (FOR 8DPSK)	145
12.1 FREQUENCY ERROR	145
12.2 ANTENNA POWER	147
12.3 UNWANTED EMISSION STRENGTH	148
12.4 OCCUPIED BANDWIDTH –NORMAL (99%).....	151
12.5 SPREAD-SPECTRUM BANDWIDTH –NORMAL (90%)	152
12.6 OCCUPIED BANDWIDTH –AFH-(99%)	153
12.7 SPREAD-SPECTRUM BANDWIDTH –AFH(90%)	154
12.8 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER	155
12.9 DWELL TIME	157
13. TEST RESULT FOR BLE 1M (CH0~CH39)(FOR GFSK)	158
13.1 FREQUENCY ERROR	158
13.2 ANTENNA POWER	160
13.3 UNWANTED EMISSION STRENGTH	162
13.4 OCCUPIED BANDWIDTH (99%)	170
13.5 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER	172
14. TEST RESULT FOR BLE 2M (CH0~CH39)(FOR GFSK)	176

Report No.: TMWK2305001503KR

Rev. 00

14.1	FREQUENCY ERROR	176
14.2	ANTENNA POWER	178
14.3	UNWANTED EMISSION STRENGTH	180
14.4	OCCUPIED BANDWIDTH (99%)	188
14.5	LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER	190
15.	INTERFERENCE PREVENTION FUNCTION.....	194
	APPENDIX A - PHOTOGRAPHS OF TEST SETUP	A-1

1. TEST RESULT CERTIFICATION

Applicant: TechNexion Ltd.
16F-5, No. 736, Zhongzheng Road, ZhongHe District,
23511, New Taipei City, Taiwan

Manufacturer: TechNexion Ltd.
16F-5, No. 736, Zhongzheng Road, ZhongHe District,
23511, New Taipei City, Taiwan

Equipment Under Test: WiFi+Bluetooth 5.2 System on Module

Trade Name: TechNexion

Model Number: PIXI-IW416

Detailed EUT Description: See Item 3 of this report

EUT Receive Date: May 16, 2023

Date of Test: May 22~24, 2023

Report No.: TMWK2305001503KR

APPLICABLE STANDARDS	
CLASSIFICATION	TEST RESULT
ARIB STD T-66 Ver.3.7	Compliance
Statements of Conformity	
Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	

The above equipment was tested by Compliance Certification Services Inc. for compliance with the requirements set forth in ARIB STD T-66 Ver.3.7. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Measurement was conducted by the following test method: the test method of Ordinance Concerning Technical Regulations Conformity Certification etc. of Specified Radio Equipment in Annex 1, the Ministry of Internal Affairs and Communication notification in Annex 43 of Article 88, the Paragraph 1 test method more than equivalent.

Approved by:



Shawn Wu
Supervisor
Compliance Certification Services Inc.

Report No.: TMWK2305001503KR

2. SUMMARY OF TEST RESULTS

2.1 WLAN IEEE 802.11b (CH1~CH13)

APPLIED STANDARD: ARIB STD T-66 Ver.3.7			
Standard Section	Report Section	Test Type and Limit	Test Result
General provisions			
5	6.1	Frequency Tolerance	PASS
6	6.4	Occupied Bandwidth	PASS
7	6.3	Unwanted Emission Strength	PASS
Transmitting equipment			
14	6.2	RF Out Power	PASS
14.2	-	SAR	-
Transmitting antenna			
20	3	Type, Configuration, etc., of Transmitting Antenna	PASS
22	-	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS
Receiving antenna			
24	6.6	Limitation of Collateral Emission of Receiver	PASS
26	3	Refer to All Articles for Transmitting Antenna	PASS
Operating frequency 2400~2483MHz			
49.20(1);a	4.4	RF Shielding Method	PASS
49.20(1);a	3	Communication Method	PASS
49.20(1);b	-	Spread-spectrum Method	-
49.20(1);c	6.2	RF Out Power	PASS
49.20(1);d	-	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS
49.20(1);e	6.5	Spread-Spectrum Bandwidth	PASS
49.20(1);f	6.5	Spreading Factor	PASS
49.20(1);g	-	Hopping Frequency Dwell Time (FH employed)	-
-	15	Interference Prevention Function	PASS

Report No.: TMWK2305001503KR

2.2 WLAN IEEE 802.11g (CH1~CH13)

APPLIED STANDARD: ARIB STD T-66 Ver.3.7			
Standard Section	Report Section	Test Type and Limit	Test Result
General provisions			
5	7.1	Frequency Tolerance	PASS
6	7.4	Occupied Bandwidth	PASS
7	7.3	Unwanted Emission Strength	PASS
Transmitting equipment			
14	7.2	RF Out Power	PASS
14.2	-	SAR	-
Transmitting antenna			
20	3	Type, Configuration, etc., of Transmitting Antenna	PASS
22	-	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS
Receiving antenna			
24	7.5	Limitation of Collateral Emissions of Receiver	PASS
26	3	Refer to All Articles for Transmitting Antenna	PASS
Operating frequency 2400~2483MHz			
49.20(1);a	4.4	RF Shielding Method	PASS
49.20(1);a	3	Communication Method	PASS
49.20(1);b	-	Spread-spectrum Method	-
49.20(1);c	7.2	RF Out Power	PASS
49.20(1);d	-	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS
49.20(1);e	-	Diffusion Bandwidth	PASS
49.20(1);f	-	Spreading Factor	PASS
49.20(1);g	-	Hopping Frequency Dwell Time (FH employed)	-
-	15	Interference Prevention Function	PASS

Report No.: TMWK2305001503KR

2.4 WLAN IEEE 802.11n HT20 (CH1~CH13)

APPLIED STANDARD: ARIB STD T-66 Ver.3.7			
Standard Section	Report Section	Test Type and Limit	Test Result
General provisions			
5	8.1	Frequency Tolerance	PASS
6	8.4	Occupied Bandwidth	PASS
7	8.3	Unwanted Emission Strength	PASS
Transmitting equipment			
14	8.2	RF Out Power	PASS
14.2	-	SAR	-
Transmitting antenna			
20	3	Type, Configuration, etc., of Transmitting Antenna	PASS
22	-	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS
Receiving antenna			
24	8.5	Limitation of Collateral Emissions of Receiver	PASS
26	3	Refer to All Articles for Transmitting Antenna	PASS
Operating frequency 2400~2483MHz			
49.20(1);a	4.4	RF Shielding Method	PASS
49.20(1);a	3	Communication Method	PASS
49.20(1);b	-	Spread-spectrum Method	-
49.20(1);c	8.2	RF Out Power	PASS
49.20(1);d	-	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS
49.20(1);e	-	Diffusion Bandwidth	PASS
49.20(1);f	-	Spreading Factor	PASS
49.20(1);g	-	Hopping Frequency Dwell Time (FH employed)	-
-	15	Interference Prevention Function	PASS

Report No.: TMWK2305001503KR

2.5 WLAN IEEE 802.11n HT40 (CH3~CH11)

APPLIED STANDARD: ARIB STD T-66 Ver.3.7			
Standard Section	Report Section	Test Type and Limit	Test Result
General provisions			
5	9.1	Frequency Tolerance	PASS
6	9.4	Occupied Bandwidth	PASS
7	9.3	Unwanted Emission Strength	PASS
Transmitting equipment			
14	9.2	RF Out Power	PASS
14.2	-	SAR	-
Transmitting antenna			
20	3	Type, Configuration, etc., of Transmitting Antenna	PASS
22	-	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS
Receiving antenna			
24	9.5	Limitation of Collateral Emissions of Receiver	PASS
26	3	Refer to All Articles for Transmitting Antenna	PASS
Operating frequency 2400~2483MHz			
49.20(1);a	4.4	RF Shielding Method	PASS
49.20(1);a	3	Communication Method	PASS
49.20(1);b	-	Spread-spectrum Method	-
49.20(1);c	9.2	RF Out Power	PASS
49.20(1);d	-	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS
49.20(1);e	-	Diffusion Bandwidth	PASS
49.20(1);f	-	Spreading Factor	PASS
49.20(1);g	-	Hopping Frequency Dwell Time (FH employed)	-
-	15	Interference Prevention Function	PASS

2.6 BLUETOOTH (CH0~CH78) (FOR GFSK)

APPLIED STANDARD:ARIB STD T-66 Ver.3.7			
Standard Section	Report Section	Test Type and Limit	Test Result
General provisions			
5	10.1	Frequency Error	PASS
6	10.4	Occupied Bandwidth	PASS
7	10.3	Unwanted Emission Strength	PASS
Transmitting equipment			
14	10.2	Antenna Power	PASS
14.2	-	SAR	-
Transmitting antenna			
20	3	Type, Configuration, etc., of Transmitting Antenna	PASS
22	-	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS
Receiving antenna			
24	10.8	Limitation of Collateral Emission of Receiver	PASS
26	3	Refer to All Articles for Transmitting Antenna	PASS
Operating frequency 2400~2483MHz			
49.20(1);a	4.4	RF Shielding Method	PASS
49.20(1);a	3	Communication Method	PASS
49.20(1);b	3	Spread-spectrum Method	PASS
49.20(1);d	-	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS
49.20(1);e	10.5	Spread-Spectrum Bandwidth	PASS
49.20(1);g	10.9	Hopping Frequency Dwell Time (FH employed)	PASS
-	15	Interference Prevention Function	PASS

2.7 BLUETOOTH (CH0~CH78) (For $\pi/4$ DQPSK)

APPLIED STANDARD:ARIB STD T-66 Ver.3.7			
Standard Section	Report Section	Test Type and Limit	Test Result
General provisions			
5	11.1	Frequency Error	PASS
6	11.4	Occupied Bandwidth	PASS
7	11.3	Unwanted Emission Strength	PASS
Transmitting equipment			
14	11.2	Antenna Power	PASS
14.2	-	SAR	-
Transmitting antenna			
20	3	Type, Configuration, etc., of Transmitting Antenna	PASS
22	-	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS
Receiving antenna			
24	11.8	Limitation of Collateral Emission of Receiver	PASS
26	3	Refer to All Articles for Transmitting Antenna	PASS
Operating frequency 2400~2483MHz			
49.20(1);a	4.4	RF Shielding Method	PASS
49.20(1);a	3	Communication Method	PASS
49.20(1);b	3	Spread-spectrum Method	PASS
49.20(1);d	-	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS
49.20(1);e	11.5	Spread-Spectrum Bandwidth	PASS
49.20(1);g	11.9	Hopping Frequency Dwell Time (FH employed)	PASS
-	15	Interference Prevention Function	PASS

2.8 BLUETOOTH (CH0~CH78) (FOR 8DPSK)

APPLIED STANDARD:ARIB STD T-66 Ver.3.7			
Standard Section	Report Section	Test Type and Limit	Test Result
General provisions			
5	12.1	Frequency Error	PASS
6	12.4	Occupied Bandwidth	PASS
7	12.3	Unwanted Emission Strength	PASS
Transmitting equipment			
14	12.2	Antenna Power	PASS
14.2	-	SAR	-
Transmitting antenna			
20	3	Type, Configuration, etc., of Transmitting Antenna	PASS
22	-	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS
Receiving antenna			
24	12.8	Limitation of Collateral Emission of Receiver	PASS
26	3	Refer to All Articles for Transmitting Antenna	PASS
Operating frequency 2400~2483MHz			
49.20(1);a	4.4	RF Shielding Method	PASS
49.20(1);a	3	Communication Method	PASS
49.20(1);b	3	Spread-spectrum Method	PASS
49.20(1);d	-	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS
49.20(1);e	12.5	Spread-Spectrum Bandwidth	PASS
49.20(1);g	12.9	Hopping Frequency Dwell Time (FH employed)	PASS
-	15	Interference Prevention Function	PASS

2.9 BLE 1M (CH0~CH39) (FOR GFSK)

APPLIED STANDARD:ARIB STD T-66 Ver.3.7			
Standard Section	Report Section	Test Type and Limit	Test Result
General provisions			
5	13.1	Frequency Error	PASS
6	13.4	Occupied Bandwidth	PASS
7	13.3	Spurious Emissions Intensity	PASS
Transmitting equipment			
14	13.2	Antenna Power	PASS
14.2	-	SAR	-
Transmitting antenna			
20	3	Type, Configuration, etc., of Transmitting Antenna	PASS
22	-	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS
Receiving antenna			
24	13.5	Limitation of Collateral Emission of Receiver	PASS
26	3	Refer to All Articles for Transmitting Antenna	PASS
Operating frequency 2400~2483MHz			
49.20(1);a	4.4	RF Shielding Method	PASS
49.20(1);a	3	Communication Method	PASS
49.20(1);b	3	Spread-spectrum Method	PASS
49.20(1);d	-	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS
49.20(1);e	-	Spread-Spectrum Bandwidth	-
-	15	Interference Prevention Function	PASS

2.10 BLE 2M (CH0~CH39) (FOR GFSK)

APPLIED STANDARD:ARIB STD T-66 Ver.3.7			
Standard Section	Report Section	Test Type and Limit	Test Result
General provisions			
5	14.1	Frequency Error	PASS
6	14.4	Occupied Bandwidth	PASS
7	14.3	Spurious Emissions Intensity	PASS
Transmitting equipment			
14	14.2	Antenna Power	PASS
14.2	-	SAR	-
Transmitting antenna			
20	3	Type, Configuration, etc., of Transmitting Antenna	PASS
22	-	Direction Pattern of Transmitting Antenna (Provided at Individual Antenna Report)	PASS
Receiving antenna			
24	14.5	Limitation of Collateral Emission of Receiver	PASS
26	3	Refer to All Articles for Transmitting Antenna	PASS
Operating frequency 2400~2483MHz			
49.20(1);a	4.4	RF Shielding Method	PASS
49.20(1);a	3	Communication Method	PASS
49.20(1);b	3	Spread-spectrum Method	PASS
49.20(1);d	-	Absolute Antenna Gain (Provided at Individual Antenna Report)	PASS
49.20(1);e	-	Spread-Spectrum Bandwidth	-
-	15	Interference Prevention Function	PASS

Report No.: TMWK2305001503KR

3. EUT DESCRIPTION

Product	WiFi+Bluetooth 5.2 System on Module		
Model Number	PIXI-IW416		
Trade Name	TechNexion		
Power Supply	5VDC from Host PC Power Supply		
Model Discrepancy	N/A		
Frequency Range	IEEE 802.11b (CH1~13): 2412~2472MHz IEEE 802.11g (CH1~13): 2412~2472MHz IEEE 802.11n HT20 (CH1~13): 2412~2472MHz IEEE 802.11n HT40 (CH3~11): 2422~2462MHz Bluetooth: 2402~2480MHz		
Rated Antenna Power (mW, mW/MHz)	IEEE 802.11b (CH1~13):	6.356	mW/MHz
	IEEE 802.11g (CH1~13)	2.961	mW/MHz
	IEEE 802.11n HT20 (CH1~13)	1.617	mW/MHz
	IEEE 802.11n HT40 (CH3~11)	0.881	mW/MHz
	Bluetooth 2.0 for GFSK(Normal):	0.053	mW/MHz
	Bluetooth 2.0 for GFSK(AFH):	0.208	mW/MHz
	Bluetooth 2.0 for π /4DQPSK (Normal):	0.056	mW/MHz
	Bluetooth 2.0 for π /4DQPSK (AFH):	0.219	mW/MHz
	Bluetooth 2.0 for 8DPSK(Normal):	0.051	mW/MHz
	Bluetooth 2.0 for 8DPSK(AFH):	0.197	mW/MHz
	BLE 1M:	6.331	mW
	BLE 2M:	6.039	mW
	Measured Antenna Power (mW, mW/MHz)	IEEE 802.11b (CH1~13):	6.356
IEEE 802.11g (CH1~13)		2.961	mW/MHz
IEEE 802.11n HT20 (CH1~13)		1.617	mW/MHz
IEEE 802.11n HT40 (CH3~11)		0.881	mW/MHz
Bluetooth 2.0 for GFSK(Normal):		0.053	mW/MHz
Bluetooth 2.0 for GFSK(AFH):		0.208	mW/MHz
Bluetooth 2.0 for π /4DQPSK (Normal):		0.056	mW/MHz
Bluetooth 2.0 for π /4DQPSK (AFH):		0.219	mW/MHz
Bluetooth 2.0 for 8DPSK(Normal):		0.051	mW/MHz
Bluetooth 2.0 for 8DPSK(AFH):		0.197	mW/MHz
BLE 1M:		6.331	mW
BLE 2M:		6.039	mW

Report No.: TMWK2305001503KR

Modulation Technique	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (QPSK, BPSK, 16-QAM, 64-QAM) IEEE 802.11n: OFDM (QPSK, BPSK, 16-QAM, 64-QAM) Bluetooth: FHSS (GFSK, $\pi/4$ -DQPSK, 8DPSK) BLE 1M & BLE 2M: GFSK
Number of Channels	IEEE 802.11b (CH1~13): 13 channels IEEE 802.11g / n HT20 (CH1~13): 13 channels IEEE 802.11n HT40 (CH3~11): 9 channels Bluetooth (CH0~78): 79 channels BLE 1M & BLE 2M: 40 channels
Antenna Specification	1. Dipole Antenna / Gain: 4 dBi (*Worst) 2. PIFA Antenna / Gain: 2.5 dBi
Hardware Version	A1
Software Version	1.0

Remark:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

Report No.: TMWK2305001503KR

4. TEST METHODOLOGY & CONDITIONS

4.1 TEST CONDITIONS

Temperature: 24.3~25.2°C

Test date: May 22~24, 2023

Humidity: 50~60% RH

Tested by: David Li, Marco Chan

WIFI 2.4GHz

	unit	----	----	----	Limit	Result
Ambient Temperature	°C	25.2			\geq 5 \leq 35	PASS
Relative Humidity	%	60			\geq 45 \leq 85	PASS
Input Power Voltage	VDC	3.3			----	----
The reason why the tests are performed only at rated voltage:	When the input voltage to receiver RF circuit varies below \pm 1% as the input voltage from the external power supply to the receiver varies \pm 10% (excluding power supply).					

802.11b	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Declaration Output Power	mW/MHz	6.356			\leq 10	PASS
	dBm/MHz	8.032			\leq 10	PASS
E.I.R.P.	dBm/MHz	12.03			< 12.14	PASS
Peak Antenna Gain (Chain0)	dBi	4.00			----	----
Tested Circuit Insertion Loss (Chain0)	dB	10.50			----	----
Tested Circuit Insertion Loss (RX_Chain0)	dB	0.50			----	----
Interference Prevention Function	----	PASS	PASS	PASS	----	PASS
802.11g	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Declaration Output Power	mW/MHz	2.961			\leq 10	PASS
	dBm/MHz	4.71			\leq 10	PASS
E.I.R.P.	dBm/MHz	8.71			< 12.14	PASS
Peak Antenna Gain (Chain0)	dBi	4.00			----	----
Tested Circuit Insertion Loss (Chain0)	dB	10.50			----	----
Tested Circuit Insertion Loss (RX_Chain0)	dB	0.50			----	----
Interference Prevention Function	----	PASS	PASS	PASS	----	PASS

Report No.: TMWK2305001503KR

802.11n_20MHz		unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----	----
Channel Number	Ch.	1	7	13	----	----	----
Declaration Output Power	mW/MHz	1.617			≤	10	PASS
	dBm/MHz	2.087			≤	10	PASS
E.I.R.P.	dBm/MHz	6.09			<	12.14	PASS
Peak Antenna Gain (Chain0)	dBi	4.00			----	----	----
Tested Circuit Insertion Loss (Chain0)	dB	10.50			----	----	----
Tested Circuit Insertion Loss (RX_Chain0)	dB	0.50			----	----	----
Interference Prevention Function	----	PASS	PASS	PASS	----	----	PASS
802.11n_40MHz		unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2422	2442	2462	----	----	----
Channel Number	Ch.	3	7	11	----	----	----
Declaration Output Power	mW/MHz	0.881			≤	5	PASS
	dBm/MHz	-0.550			≤	6.99	PASS
E.I.R.P.	dBm/MHz	3.45			<	9.13	PASS
Peak Antenna Gain (Chain0)	dBi	4.00			----	----	----
Tested Circuit Insertion Loss (Chain0)	dB	10.50			----	----	----
Tested Circuit Insertion Loss (RX_Chain0)	dB	0.50			----	----	----
Interference Prevention Function	----	PASS	PASS	PASS	----	----	PASS

Bluetooth for GFSK

		Limit	Result	Note	
Environment of Test	Temperature	°C	24.3	$5 \leq x \leq 35$	PASS
Room	Humidity	%	50	$45 \leq x \leq 85$	PASS
Peak Antenna Gain	dBi	4	----	----	----
Number of hopping channel	----	79	20	----	----
Declaration Output Power	mW/MHz	0.053	0.208	≤ 3 mW/MHz	PASS
Declaration Output Power	dBm/MHz	-12.76	-6.82	≤ 4.77 dBm/MHz	PASS
E.I.R.P.	dBm/MHz	-8.76	-2.82	≤ 6.91 dBm/MHz	PASS
Tested Circuit Insertion Loss	dB	0.50	0.50	----	----
Input Voltage	VDC	3.30		----	----
Packet Type (Mode)	----	DH5		----	----
Frequency equal to the transmission rate of the modulation signal	MHz	1		----	----
Test Category	2.4GHz Band Wideband Low-Power Data Communication System (Bluetooth GFSK include AFH)				
The reason why test are performed only rated voltage					
When the input voltage to receiver RF circuit varies below $\pm 1\%$ as the input voltage from the external power supply to the receiver varies $\pm 10\%$ (excluding power supply).					

Report No.: TMWK2305001503KR

Bluetooth for $\pi/4$ DQPSK

				Limit	Result	Note
Environment of Test	Temperature	°C	24.3	$5 \leq x \leq 35$	PASS	
Room	Humidity	%	50	$45 \leq x \leq 85$	PASS	
Peak Antenna Gain	dBi		4	-----	-----	
Number of hopping channel	-----	79	20	-----	-----	
Declaration Output Power	mW/MHz	0.056	0.219	≤ 3 mW/MHz	PASS	
Declaration Output Power	dBm/MHz	-12.52	-6.60	≤ 4.77 dBm/MHz	PASS	
E.I.R.P.	dBm/MHz	-8.52	-2.60	≤ 6.91 dBm/MHz	PASS	
Tested Circuit Insertion Loss	dB	0.50	0.50	-----	-----	
Input Voltage	VDC		3.30	-----	-----	
Packet Type (Mode)	-----		2DH5	-----	-----	
Frequency equal to the transmission rate of the modulation signal	MHz		1	-----	-----	
Test Category	2.4GHz Band Wideband Low-Power Data Communication System (Bluetooth $\pi/4$ -DQPSK include AFH)					
The reason why test are performed only rated voltage						
When the input voltage to receiver RF circuit varies below $\pm 1\%$ as the input voltage from the external power supply to the receiver varies $\pm 10\%$ (excluding power supply).						

Bluetooth for 8DPSK

				Limit	Result	Note
Environment of Test	Temperature	°C	24.3	$5 \leq x \leq 35$	PASS	
Room	Humidity	%	50	$45 \leq x \leq 85$	PASS	
Peak Antenna Gain	dBi		4	-----	-----	
Number of hopping channel	-----	79	20	-----	-----	
Declaration Output Power	mW/MHz	0.051	0.197	≤ 3 mW/MHz	PASS	
Declaration Output Power	dBm/MHz	-12.92	-7.06	≤ 4.77 dBm/MHz	PASS	
E.I.R.P.	dBm/MHz	-8.92	-3.06	≤ 6.91 dBm/MHz	PASS	
Tested Circuit Insertion Loss	dB	0.50	0.50	-----	-----	
Input Voltage	VDC		3.30	-----	-----	
Packet Type (Mode)	-----		3DH5	-----	-----	
Frequency equal to the transmission rate of the modulation signal	MHz		1	-----	-----	
Test Category	2.4GHz Band Wideband Low-Power Data Communication System (Bluetooth 8DPSK include AFH)					
The reason why test are performed only rated voltage						
When the input voltage to receiver RF circuit varies below $\pm 1\%$ as the input voltage from the external power supply to the receiver varies $\pm 10\%$ (excluding power supply).						

BLE 1M

Environment of Test Room	Temperature	24.8~25.2	°C
	Humidity	52~60	%

Peak Antenna Gain	4	dBi
Declaration Output Power	6.331	mW
Declaration Output Power	8.015	dBm
E.I.R.P.	12.015	dBm
Input Voltage	3.3	VDC

BLE 2M

Environment of Test Room	Temperature	24.8~25.2	°C
	Humidity	52~60	%

Peak Antenna Gain	4	dBi
Declaration Output Power	6.039	mW
Declaration Output Power	7.810	dBm
E.I.R.P.	11.810	dBm
Input Voltage	3.3	VDC

Report No.: TMWK2305001503KR

Voltage Fluctuation Test	Normal Voltage	High Voltage + 10% of Normal Voltage	Low Voltage - 10% of Normal Voltage
Input AC Power	3.3	3.63	2.97
Output DC Power	3.3	3.3	3.3
Voltage Variation (%)	0	0	0
Note: Voltage Variation (%) = (Output High or Low Voltage - Output Normal Voltage)/Output Normal Voltage X 100			
During the input supply voltage to the EUT from the external power source is varied by +/- 10%, if output voltage had been confirmed that the fluctuation of power supply to the RF circuit of EUT (excluding power source) is equal to or less than +/- 1%. Exempt extremely high and low supply voltage condition tests, EUT only operated in normal voltage to test all regulations.			

4.2 DESCRIPTION OF TEST MODES

The EUT (model: PIXI-IW416) had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

The worst case data rate is determined as the data rate with highest output power.

IEEE802.11b (CH1~13): Channel Low, Channel Mid and Channel High with 11Mbps data rate were chosen for full testing.

IEEE802.11g (CH1~13): Channel Low, Channel Mid and Channel High with 6Mbps data rate were chosen for full testing.

IEEE802.11n HT 20MHz (CH1~13) : Channel Low, Channel Mid and Channel High with 6.5Mbps data rate were chosen for full testing.

IEEE802.11n HT40 (CH3~11): Channel Low, Channel Mid and Channel High with 13.5Mbps data rate were chosen for full testing.

Bluetooth & BLE: Measurement was conducted by the following test method.

4.3 TESTING APPLIED STARDARDS


MIC Notice No.88 Appendix No.43

MIC Certification Rule, Article 2 Paragraph 1 Item 19

ARIB STD-66

4.4 RF SHIELDING METHOD

The RF part is not easily accessible because the EUT is using a shielding case as below.



4.5 SETUP OF EQUIPMENT UNDER TEST

Setup Diagram

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

Support Equipment

No	Equipment	Trade Name	Model	Serial No.	FCC ID
1.	NB(G)	Lenovo	T460P	N/A	N/A

Report No.: TMWK2305001503KR

5. INSTRUMENT AND CALIBRATION

5.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

5.2 TEST AND MEASUREMENT EQUIPMENT

The following list contains measurement equipment used for testing. The equipment conforms to the requirement of CISPR 16-1, ANSI C63.2 and other equivalent standards.

Calibration of all test and measurement, including any accessories that may effect such calibration, is checked frequently to ensure the accuracy. Adjustments are made and correction factors are applied in accordance with the instructions contained in the respective manual.

Equipment Used for Emission Measurement

Conducted Emission Test Site								
Name of Equipment	Manufacturer	Model	Serial Number	Cal Date	Cal Due	Calibration Lab.	Accreditation Organization of the Cal. Lab	Calibration Method
SG	Keysight	E8257C	US42340383	2022-06-29	2023-06-28	ETC	TAF	c
Power Meter	Anritsu	ML2496A	2136002	2022-11-24	2023-11-23	ETC	TAF	c
EXA Signal Analyzer	Keysight	N9010B	MY60242460	2023-02-02	2024-02-01	ETC	TAF	c
Power Sensor	Anritsu	MA2411B	1911386	2022-08-08	2023-08-07	ETC	TAF	c
Power Sensor	Anritsu	MA2411B	1911387	2022-08-08	2023-08-07	ETC	TAF	c
Software	Radio Test Software Ver. 21							

Remark:

1. Each piece of equipment is scheduled for calibration once a year.
2. Calibration Method:
 - a) Calibration conducted by the National Institute of Information and Communications Technology (NICT) (hereinafter referred to as "NICT") or a designated calibration agency under Article 102-18 paragraph (1)
 - b) Correction conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992)
 - c) Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1)
 - d) Calibration conducted by using measuring instruments and other equipment listed in the right column of Table No. 3 attached hereto, which shall have been given any of calibration, etc. listed above from a) to c)

Report No.: TMWK2305001503KR

5.3 MEASUREMENT UNCERTAINTY

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028-1 [2] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 6 is based on such expansion factors.

Table: Maximum measurement uncertainty

PARAMETER	UNCERTAINTY
RF Output Power	± 1.871 dB
Frequency Tolerance	± 0.03 ppm
Unwanted Emission strength	± 1.875 dB
Occupied Bandwidth (99%)	± 1.9 %
Spread-Spectrum Bandwidth (90%)	± 1.9 %
Limitation of collateral emissions of receiver	± 1.875 dB

Remark:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

Report No.: TMWK2305001503KR

6. TEST RESULT FOR IEEE 802.11b (CH1~CH13)


6.1 FREQUENCY ERROR

TEST RESULT

Frequency Tolerance						
802.11b	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Reading Frequency (Chain0)	MHz	2412.013	2442.015	2472.016	\geq -50.00	PASS
Frequency Tolerance (Chain0)	ppm	5.38972	6.14251	6.47249	\leq 50.00	

TEST PLOTS

Chain 0 / CH Low




Report No.: TMWK2305001503KR

Chain 0 / CH Mid



Chain 0 / CH High



Report No.: TMWK2305001503KR

6.2 RF OUTPUT POWER

TEST RESULT


RF Output Power						
802.11b	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
RF Output Power (Chain0)	mW/MHz	6.356	5.418	5.594	≤ 10.000	PASS
	dBm/MHz	8.0316	7.3384	7.4772	≤ 10.000	
RF Output Power Tolerance	%	-0.01	-14.76	-11.99	≤ 20	PASS
					≥ -80	

TEST PLOTS


Chain 0 / CH Low



Chain 0 / CH Mid



Chain 0 / CH High



Report No.: TMWK2305001503KR


6.3 UNWANTED EMISSION STRENGTH

TEST RESULT


Unwanted Emission Strength (Chain 0&1)						
802.11b	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Under 2387MHz (Chain0)	μW/MHz	0.1995	0.2046	0.3690	≤ 2.50	PASS
	MHz	2159.50	2375.30	105.90	----	
2387 ~ 2400MHz (Chain0)	μW/MHz	0.4335	0.1702	0.1486	≤ 25.00	PASS
	MHz	2398.50	2395.52	2387.65	----	
2483.5 ~ 2496.5MHz (Chain0)	μW/MHz	0.1567	0.2070	0.4416	≤ 25.00	PASS
	MHz	2490.95	2487.17	2483.50	----	
2496.5MHz ~ 12.5GHz (Chain0)	μW/MHz	0.3381	0.2979	0.2685	≤ 2.50	PASS
	MHz	3618.00	3785.00	3707.00	----	

Report No.: TMWK2305001503KR

Under 2387MHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Mid





Report No.: TMWK2305001503KR

Chain 0 / CH High




Report No.: TMWK2305001503KR


2387 ~ 2400MHz (Chain0) TEST PLOTS Chain 0 / CH Low



Chain 0 / CH Mid




Chain 0 / CH High




Report No.: TMWK2305001503KR

2483.5 ~ 2496.5MHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Mid





Report No.: TMWK2305001503KR

Chain 0 / CH High




Report No.: TMWK2305001503KR


2496.5MHz ~ 12.5GHz (Chain0)

TEST PLOTS

Chain 0 / CH Low



Chain 0 / CH Mid



Chain 0 / CH High



6.4 OCCUPIED BANDWIDTH (99%)

TEST RESULT


Occupied Bandwidth						
802.11b	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Occupied Bandwidth (Chain0)	MHz	11.955	11.969	11.981	≤ 26	PASS

Report No.: TMWK2305001503KR

TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Mid



Report No.: TMWK2305001503KR

Chain 0 / CH High





Report No.: TMWK2305001503KR

Page 43 / 193

Rev. 00

6.5 SPREAD-SPECTRUM BANDWIDTH (90%)

TEST RESULT


Spread Bandwidth & Spreading Factor						
802.11b	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Spread Bandwidth (Chain0)_11 Mbps	MHz	8.62240	8.64270	8.62630	\geq 0.5	PASS
Spread Factor (Chain0)	----	6.27	6.29	6.27	\geq 5.00	
Spread Factor =Spread Bandwidth / Symbol Rate(1.375Mbps)						

Report No.: TMWK2305001503KR

TEST PLOTS Chain 0 / CH Low



Chain 0 / CH Mid



Report No.: TMWK2305001503KR

Chain 0 / CH High





Report No.: TMWK2305001503KR

Page 46 / 193

Rev. 00


6.6 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER

TEST RESULT


Secondarily emitted radio wave strength						
802.11b	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Under 1GHz (Chain0)	nW	1.387	2.014	0.764	≤ 4.00	PASS
	MHz	101.80	101.80	106.00	----	
1 - 12.5GHz (Chain0)	nW	0.044	0.081	0.177	≤ 20.00	PASS
	MHz	3283.00	2480.00	2426.00	----	

Report No.: TMWK2305001503KR

Under 1GHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Low (Sample)




Report No.: TMWK2305001503KR

Chain 0 / CH Mid




Chain 0 / CH Mid (Sample)




Report No.: TMWK2305001503KR

Chain 0 / CH High



Chain 0 / CH High (Sample)




Report No.: TMWK2305001503KR

1 - 12.5GHz (Chain0) TEST PLOTS Chain 0 / CH Low



Chain 0 / CH Mid



Report No.: TMWK2305001503KR

Chain 0 / CH High



Report No.: TMWK2305001503KR

7. TEST RESULT FOR IEEE 802.11g (CH1~CH13)


7.1 FREQUENCY ERROR

TEST RESULT

Frequency Tolerance						
802.11g	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Reading Frequency (Chain0)	MHz	2412.012	2442.013	2472.015	\geq -50.00	PASS
Frequency Tolerance (Chain0)	ppm	4.97512	5.32351	6.06796	\leq 50.00	


TEST PLOTS

Chain 0 / CH Low




Report No.: TMWK2305001503KR

Chain 0 / CH Mid



Chain 0 / CH High



Report No.: TMWK2305001503KR


7.2 RF OUTPUT POWER

TEST RESULT

RF Output Power						
802.11g	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
RF Output Power (Chain0)	mW/MHz	2.961	2.233	1.590	≤ 10.000	PASS
	dBm/MHz	4.7139	3.4892	2.0137	≤ 10.000	
RF Output Power Tolerance	%	-0.01	-24.58	-46.31	≤ 20	PASS
					≥ -80	


TEST PLOTS

Chain 0 / CH Low




Report No.: TMWK2305001503KR

Chain 0 / CH Mid



Chain 0 / CH High





Report No.: TMWK2305001503KR

7.3 UNWANTED EMISSION STRENGTH

TEST RESULT


Unwanted Emission Strength (Chain 0&1)						
802.11b	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Under 2387MHz (Chain0)	μW/MHz	0.1995	0.2046	0.3690	≤ 2.50	PASS
	MHz	2159.50	2375.30	105.90	----	
2387 ~ 2400MHz (Chain0)	μW/MHz	0.4335	0.1702	0.1486	≤ 25.00	PASS
	MHz	2398.50	2395.52	2387.65	----	
2483.5 ~ 2496.5MHz (Chain0)	μW/MHz	0.1567	0.2070	0.4416	≤ 25.00	PASS
	MHz	2490.95	2487.17	2483.50	----	
2496.5MHz ~ 12.5GHz (Chain0)	μW/MHz	0.3381	0.2979	0.2685	≤ 2.50	PASS
	MHz	3618.00	3785.00	3707.00	----	

Report No.: TMWK2305001503KR


Under 2387MHz (Chain0)

TEST PLOTS


Chain 0 / CH Low



Chain 0 / CH Mid




Chain 0 / CH High




Report No.: TMWK2305001503KR

2387 ~ 2400MHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Low (Sample)




Report No.: TMWK2305001503KR

Chain 0 / CH Mid




Chain 0 / CH High




Report No.: TMWK2305001503KR

2483.5 ~ 2496.5MHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Mid




Report No.: TMWK2305001503KR

Chain 0 / CH High



Chain 0 / CH High (Sample)




Report No.: TMWK2305001503KR


2496.5MHz ~ 12.5GHz (Chain0)

TEST PLOTS

Chain 0 / CH Low




Chain 0 / CH Mid





Report No.: TMWK2305001503KR

Chain 0 / CH High





Report No.: TMWK2305001503KR

Page 65 / 193

Rev. 00

7.4 OCCUPIED BANDWIDTH (99%)

TEST RESULT

Occupied Bandwidth						
802.11g	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Occupied Bandwidth (Chain0)	MHz	16.809	16.811	16.803	≤ 40	PASS

Report No.: TMWK2305001503KR

TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Mid



Report No.: TMWK2305001503KR

Chain 0 / CH High




7.5 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER

TEST RESULT


Secondarily emitted radio wave strength						
802.11g	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Under 1GHz (Chain0)	nW	2.104	0.918	1.019	≤ 4.00	PASS
	MHz	106.00	106.00	106.00	----	
1 - 12.5GHz (Chain0)	nW	0.134	0.075	0.044	≤ 20.00	PASS
	MHz	2441.00	2480.00	3283.00	----	

Report No.: TMWK2305001503KR

Under 1GHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Low (Sample)




Report No.: TMWK2305001503KR

Chain 0 / CH Mid




Chain 0 / CH Mid (Sample)




Report No.: TMWK2305001503KR

Chain 0 / CH High



Chain 0 / CH High (Sample)




Report No.: TMWK2305001503KR

1 - 12.5GHz (Chain0) TEST PLOTS Chain 0 / CH Low



Chain 0 / CH Mid



Report No.: TMWK2305001503KR

Chain 0 / CH High



Report No.: TMWK2305001503KR

8. TEST RESULT FOR IEEE 802.11n HT20 (CH1~CH13)


8.1 FREQUENCY ERROR

TEST RESULT

Frequency Tolerance						
802.11n_20MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Reading Frequency (Chain0)	MHz	2412.014	2442.015	2472.015	\geq -50.00	PASS
Frequency Tolerance (Chain0)	ppm	5.80431	6.14251	6.06796	\leq 50.00	


TEST PLOTS

Chain 0 / CH Low




Report No.: TMWK2305001503KR

Chain 0 / CH Mid



Chain 0 / CH High



Report No.: TMWK2305001503KR

8.2 RF OUTPUT POWER

TEST RESULT


RF Output Power						
802.11n_20MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
RF Output Power (Chain0)	mW/MHz	1.503	1.617	1.556	≤ 10.000	PASS
	dBm/MHz	1.7706	2.0877	1.9201	≤ 10.000	
RF Output Power Tolerance	%	-7.03	0.01	-3.77	≤ 20	PASS
					≥ -80	

TEST PLOTS


Chain 0 / CH Low



Chain 0 / CH Mid



Chain 0 / CH High



Report No.: TMWK2305001503KR

8.3 UNWANTED EMISSION STRENGTH

TEST RESULT


Unwanted Emission Strength (Chain 0&1)						
802.11n 20MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Under 2387MHz (Chain0)	μW/MHz	0.3999	0.2113	0.1854	≤ 2.50	PASS
	MHz	2380.90	2383.60	2174.90	----	
2387 ~ 2400MHz (Chain0)	μW/MHz	7.8705	0.2553	0.1517	≤ 25.00	PASS
	MHz	2396.23	2396.92	2387.40	----	
2483.5 ~ 2496.5MHz (Chain0)	μW/MHz	0.1671	0.3420	0.0555	≤ 25.00	PASS
	MHz	2495.74	2484.54	2483.75	----	
2496.5MHz ~ 12.5GHz (Chain0)	μW/MHz	0.2735	0.3126	0.3228	≤ 2.50	PASS
	MHz	3848.00	3793.00	3784.00	----	

Report No.: TMWK2305001503KR


Under 2387MHz (Chain0)

TEST PLOTS


Chain 0 / CH Low



Chain 0 / CH Mid



Chain 0 / CH High



Report No.: TMWK2305001503KR


2387 ~ 2400MHz (Chain0)

TEST PLOTS


Chain 0 / CH Low



Chain 0 / CH Mid




Chain 0 / CH High




Report No.: TMWK2305001503KR

2483.5 ~ 2496.5MHz (Chain0) TEST PLOTS Chain 0 / CH Low



Chain 0 / CH Mid




Report No.: TMWK2305001503KR

Chain 0 / CH High



Chain 0 / CH High (Sample)



Report No.: TMWK2305001503KR


2496.5MHz ~ 12.5GHz (Chain0)

TEST PLOTS

Chain 0 / CH Low



Chain 0 / CH Mid



Chain 0 / CH High




8.4 OCCUPIED BANDWIDTH (99%)

TEST RESULT

Occupied Bandwidth						
802.11n_20MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Occupied Bandwidth (Chain0)	MHz	17.732	17.717	17.735	≤ 40	PASS

Report No.: TMWK2305001503KR

TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Mid



Report No.: TMWK2305001503KR

Chain 0 / CH High






8.5 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER

TEST RESULT


Secondarily emitted radio wave strength						
802.11n_20MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2412	2442	2472	----	----
Channel Number	Ch.	1	7	13	----	----
Under 1GHz (Chain0)	nW	2.570	2.754	3.972	≤ 4.00	PASS
	MHz	106.00	106.00	106.00	----	
1 - 12.5GHz (Chain0)	nW	0.051	0.044	0.054	≤ 20.00	PASS
	MHz	3283.00	3283.00	3283.00	----	

Report No.: TMWK2305001503KR

Under 1GHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Low (Sample)




Report No.: TMWK2305001503KR

Chain 0 / CH Mid



Chain 0 / CH Mid (Sample)



Report No.: TMWK2305001503KR

Chain 0 / CH High



Chain 0 / CH High (Sample)



Report No.: TMWK2305001503KR

1 - 12.5GHz (Chain0) TEST PLOTS Chain 0 / CH Low



Chain 0 / CH Mid



Report No.: TMWK2305001503KR

Chain 0 / CH High



Report No.: TMWK2305001503KR

9. TEST RESULT FOR IEEE 802.11n HT40 (CH3~CH11)


9.1 FREQUENCY ERROR

TEST RESULT

Frequency Tolerance						
802.11n_40MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2422	2442	2462	----	----
Channel Number	Ch.	3	7	11	----	----
Reading Frequency (Chain0)	MHz	2422.015	2442.015	2462.015	\geq -50.00	PASS
Frequency Tolerance (Chain0)	ppm	6.19323	6.14251	6.09261	\leq 50.00	


TEST PLOTS

Chain 0 / CH Low




Report No.: TMWK2305001503KR

Chain 0 / CH Mid



Chain 0 / CH High



Report No.: TMWK2305001503KR

9.2 RF OUTPUT POWER

TEST RESULT


RF Output Power						
802.11n_40MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2422	2442	2462	----	----
Channel Number	Ch.	3	7	11	----	----
RF Output Power (Chain0)	mW/MHz	0.869	0.881	0.824	≤ 5.000	PASS
	dBm/MHz	-0.60735	-0.5499	-0.8399	≤ 6.990	
RF Output Power Tolerance	%	-1.31	0.01	-6.45	≤ 20	PASS
					≥ -80	

TEST PLOTS


Chain 0 / CH Low



Chain 0 / CH Mid



Chain 0 / CH High



Report No.: TMWK2305001503KR

9.3 UNWANTED EMISSION STRENGTH

TEST RESULT


Unwanted Emission Strength (Chain 0&1)						
802.11n_40MHz	unit	---	---	---	Limit	Result
Measurement Frequency	MHz	2422	2442	2462	---	---
Channel Number	Ch.	3	7	11	---	---
Under 2387MHz (Chain0)	μW/MHz	1.1429	1.1776	0.2339	≤ 2.50	PASS
	MHz	2384.50	724.40	102.00	---	
2387 ~ 2400MHz (Chain0)	μW/MHz	0.0735	0.8035	0.1122	≤ 25.00	PASS
	MHz	2399.85	2399.30	2398.04	---	
2483.5 ~ 2496.5MHz (Chain0)	μW/MHz	0.4198	0.9931	0.0877	≤ 25.00	PASS
	MHz	2491.06	2485.17	2483.81	---	
2496.5MHz ~ 12.5GHz (Chain0)	μW/MHz	0.2786	0.3648	0.2323	≤ 2.50	PASS
	MHz	3787.00	3742.50	5111.50	---	

Report No.: TMWK2305001503KR


Under 2387MHz (Chain0) TEST PLOTS Chain 0 / CH Low



Chain 0 / CH Mid



Chain 0 / CH High




Report No.: TMWK2305001503KR

2387 ~ 2400MHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Low (Sample)






Report No.: TMWK2305001503KR

Chain 0 / CH Mid



Chain 0 / CH High




Report No.: TMWK2305001503KR

2483.5 ~ 2496.5MHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Mid




Report No.: TMWK2305001503KR

Chain 0 / CH High



Chain 0 / CH High (Sample)




Report No.: TMWK2305001503KR


2496.5MHz ~ 12.5GHz (Chain0)

TEST PLOTS

Chain 0 / CH Low



Chain 0 / CH Mid





Report No.: TMWK2305001503KR

Chain 0 / CH High





Report No.: TMWK2305001503KR

Page 109 / 193

Rev. 00


9.4 OCCUPIED BANDWIDTH (99%)

TEST RESULT


Occupied Bandwidth						
802.11n_40MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2422	2442	2462	----	----
Channel Number	Ch.	3	7	11	----	----
Occupied Bandwidth (Chain0)	MHz	36.121	36.129	36.128	\leq 40	PASS

Report No.: TMWK2305001503KR

TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Mid





Report No.: TMWK2305001503KR

Chain 0 / CH High






9.5 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER

TEST RESULT


Secondarily emitted radio wave strength						
802.11n_40MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2422	2442	2462	----	----
Channel Number	Ch.	3	7	11	----	----
Under 1GHz (Chain0)	nW	2.518	1.510	2.825	≤ 4.00	PASS
	MHz	106.00	103.40	106.00	----	
1 - 12.5GHz (Chain0)	nW	0.048	0.059	0.229	≤ 20.00	PASS
	MHz	3283.00	3424.00	2480.00	----	

Report No.: TMWK2305001503KR

Under 1GHz (Chain0) TEST PLOTS Chain 0 / CH Low



Chain 0 / CH Low (Sample)




Report No.: TMWK2305001503KR

Chain 0 / CH Mid



Chain 0 / CH Mid (Sample)




Report No.: TMWK2305001503KR

Chain 0 / CH High




Chain 0 / CH High (Sample)



Report No.: TMWK2305001503KR

1 - 12.5GHz (Chain0) TEST PLOTS Chain 0 / CH Low




Chain 0 / CH Mid



Chain 0 / CH High



9.6 CARRIER SENSE CAPABILITY



Carrier Sense						
802.11n_40MHz	unit	----	----	----	Limit	Result
Measurement Frequency	MHz	2422	2442	2462	----	----
Channel Number	Ch.	3	7	11	----	----
Interference Level	dBm	-40.89	-40.96	-41.04	----	PASS
Carrier Sense Function	----	PASS	PASS	PASS	----	

10. TEST RESULT FOR BLUETOOTH (CH0~CH78) (FOR GFSK)

10.1 FREQUENCY ERROR

TEST RESULT

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	----	----
Number of hopping channel	----	-	79	20	----	----
Reading Frequency	MHz	2402.015	2441.014	2480.015	----	----
Frequency Tolerance	ppm	6.244796	5.73535	6.048387	$-50 \leq x \leq +50$	PASS


TEST RESULT

CH Low



Report No.: TMWK2305001503KR

CH Mid



CH High



Report No.: TMWK2305001503KR

10.2 ANTENNA POWER

TEST RESULT

Measurement Frequency	MHz	2402	2441	2480	Limit	Result		
Channel Number	Ch.	0	39	78	-----	-----		
Number of hopping channel	-----	-	79	20	-----	-----		
Transmission Output Power	Calculated result	mW/MHz	-	0.053	0.208	-	≤3 mW/MHz	-----
	Tolerance	%	-	0.00	0.00	-	-80 ≤ x ≤ +20	PASS
	Measured value	dBm	-	5.7427		-	-----	-----
	On Time	msec	-	2.890		-	-----	-----
	Dwell Time	msec	-	308.265		-	≤400 msec	PASS
Burst Ratio	%	-	77.1		-	-----	-----	

TEST PLOTS

CH Mid



Report No.: TMWK2305001503KR

10.3 UNWANTED EMISSION STRENGTH

TEST RESULT


Measurement Frequency		MHz	2402	2441	2480	Limit	Result
Channel Number		Ch.	0	39	78	----	----
Number of hopping channel		----	-	79	20	----	----
Unwanted Emission Strength	Under 2387MHz	μV/MHz	-	0.046881	-	≤2.5uW/MHz	PASS
		MHz	-	739.30	-	----	----
	2387-2400MHz	μV/MHz	-	0.033343	-	≤25uW/MHz	PASS
		MHz	-	2399.39	-	----	----
	2483.5-2496.5MHz	μV/MHz	-	0.021777	-	≤25uW/MHz	PASS
		MHz	-	2484.20	-	----	----
	Over 2496.5MHz	μV/MHz	-	0.028576	-	≤2.5uW/MHz	PASS
		MHz	-	3766.50	-	----	----

TEST PLOTS Under 2387MHz CH Mid




Report No.: TMWK2305001503KR

2387-2400MHz CH Mid




2483.5-2496.5MHz CH Mid



Report No.: TMWK2305001503KR

Over 2496.5MHz CH Mid



Report No.: TMWK2305001503KR

10.4 OCCUPIED BANDWIDTH –NORMAL (99%)


TEST RESULT

BT, GFSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Occupied Bandwidth	MHz	-	78.168	19.580	≤83.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

10.5 SPREAD-SPECTRUM BANDWIDTH –NORMAL (90%)


TEST RESULT

BT, GFSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Spread Bandwidth	MHz	-	71.048	18.041	≥ 0.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

10.6 OCCUPIED BANDWIDTH –AFH-(99%)


TEST RESULT

BT, GFSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	----	----
Number of hopping channel	----	-	79	20	----	----
Occupied Bandwidth	MHz	-	78.168	19.580	≤83.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

10.7 SPREAD-SPECTRUM BANDWIDTH –AFH(90%)


TEST RESULT

BT, GFSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Spread Bandwidth	MHz	-	71.048	18.041	≥ 0.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

10.8 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER

TEST RESULT

BT, GFSK:

Measurement Frequency	MHz	2402	2441	2480	Limit	Result	
Channel Number	Ch.	0	39	78	----	----	
Number of hopping channel	----	-	79	20	----	----	
Secondarily Emitted Radio Wave Strength (RX Spurious)	Under 1GHz	nW	-	0.019099	-	≤ 4 nW	PASS
		MHz	-	106.00	-	----	----
	Over 1GHz	nW	-	0.051050	-	≤ 20 nW	PASS
		MHz	-	3250.00	-	----	----
Tested Circuit Insertion Loss for RX Spurious						1	

TEST PLOTS


Under 1GHz

CH Mid



Report No.: TMWK2305001503KR

Over 1GHz CH Mid



Report No.: TMWK2305001503KR

10.9 DWELL TIME

TEST RESULT

Measurement Frequency	MHz	2402	2441	2480	Limit	Result		
Channel Number	Ch.	0	39	78	-----	-----		
Number of hopping channel	-----	-	79	20	-----	-----		
Transmission Output Power	Calculated result	mW/MHz	-	0.053	0.208	-	≤ 3 mW/MHz	-----
	Tolerance	%	-	0.00	0.00	-	$-80 \leq x \leq +20$	PASS
	Measured value	dBm	-	5.7427		-	-----	-----
	On Time	msec	-	2.890		-	-----	-----
	Dwell Time	msec	-	308.265		-	≤ 400 msec	PASS
	Burst Ratio	%	-	77.1		-	-----	-----
Dwell Time	mSec	-	276.79		-	≤ 400 msec	PASS	

TEST PLOTS Under 1GHz CH Mid



Report No.: TMWK2305001503KR

11. TEST RESULT FOR BLUETOOTH (CH0~CH78) (FOR $\pi/4$ DQPSK)

11.1 FREQUENCY ERROR

TEST RESULT

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Reading Frequency	MHz	2402.014	2441.014	2480.015	-----	-----
Frequency Tolerance	ppm	5.828476	5.73535	6.048387	$-50 \leq x \leq +50$	PASS


TEST RESULT

CH Low



Report No.: TMWK2305001503KR

CH Mid



CH High



Report No.: TMWK2305001503KR

11.2 ANTENNA POWER

TEST RESULT

Measurement Frequency	MHz	2402	2441	2480	Limit	Result		
Channel Number	Ch.	0	39	78	----	----		
Number of hopping channel	----	-	79	20	----	----		
Transmission Output Power	Calculated result	mW/MHz	-	0.056	0.219	-	≤ 3 mW/MHz	----
	Tolerance	%	-	0.00	0.00	-	$-80 \leq x \leq +20$	PASS
	Measured value	dBm	-	5.9935		-	----	----
	On Time	msec	-	2.880		-	----	----
	Dwell Time	msec	-	307.198		-	≤ 400 msec	PASS
Burst Ratio	%	-	76.8		-	----	----	

TEST PLOTS

CH Mid



Report No.: TMWK2305001503KR


11.3 UNWANTED EMISSION STRENGTH

TEST RESULT

Measurement Frequency		MHz	2402	2441	2480	Limit	Result
Channel Number		Ch.	0	39	78	----	----
Number of hopping channel		----	-	79	20	----	----
Unwanted Emission Strength	Under 2387MHz	μW/MHz	-	0.024434	-	≤2.5uW/MHz	PASS
		MHz	-	1723.50	-	----	----
	2387-2400MHz	μW/MHz	-	0.421697	-	≤25uW/MHz	PASS
		MHz	-	2399.46	-	----	----
	2483.5-2496.5MHz	μW/MHz	-	0.014191	-	≤25uW/MHz	PASS
		MHz	-	2486.99	-	----	----
	Over 2496.5MHz	μW/MHz	-	0.027353	-	≤2.5uW/MHz	PASS
		MHz	-	3756.50	-	----	----


TEST PLOTS

Under 2387MHz CH Mid




Report No.: TMWK2305001503KR

2387-2400MHz CH Mid




2483.5-2496.5MHz CH Mid



Report No.: TMWK2305001503KR

Over 2496.5MHz CH Mid



Report No.: TMWK2305001503KR

11.4 OCCUPIED BANDWIDTH –NORMAL (99%)


TEST RESULT

BT, $\pi/4$ DQPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Occupied Bandwidth	MHz	-	78.408	19.966	≤83.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

11.5 SPREAD-SPECTRUM BANDWIDTH –NORMAL (90%)


TEST RESULT

BT, $\pi/4$ DQPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Spread Bandwidth	MHz	-	71.142	18.192	≥ 0.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

11.6 OCCUPIED BANDWIDTH –AFH-(99%)


TEST RESULT

BT, $\pi/4$ QPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	----	----
Number of hopping channel	----	-	79	20	----	----
Occupied Bandwidth	MHz	-	78.408	19.966	≤ 83.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

11.7 SPREAD-SPECTRUM BANDWIDTH –AFH(90%)


TEST RESULT

BT, $\pi/4$ DQPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Spread Bandwidth	MHz	-	71.142	18.192	≥ 0.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

11.8 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER

TEST RESULT


BT, $\pi/4$ DQPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result	
Channel Number	Ch.	0	39	78	----	----	
Number of hopping channel	----	-	79	20	----	----	
Secondarily Emitted Radio Wave Strength (RX Spurious)	Under 1GHz	nW	-	0.009397	-	≤ 4 nW	PASS
		MHz	-	106.00	-	----	----
	Over 1GHz	nW	-	0.048195	-	≤ 20 nW	PASS
		MHz	-	3250.00	-	----	----
Tested Circuit Insertion Loss for RX Spurious						1	

TEST PLOTS


Under 1GHz

CH Mid



Report No.: TMWK2305001503KR

Over 1GHz CH Mid



Report No.: TMWK2305001503KR

11.9 DWELL TIME

TEST RESULT

Measurement Frequency	MHz	2402	2441	2480	Limit	Result		
Channel Number	Ch.	0	39	78	-----	-----		
Number of hopping channel	-----	-	79	20	-----	-----		
Transmission Output Power	Calculated result	mW/MHz	-	0.056	0.219	-	≤ 3 mW/MHz	-----
	Tolerance	%	-	0.00	0.00	-	$-80 \leq x \leq +20$	PASS
	Measured value	dBm	-	5.9935		-	-----	-----
	On Time	msec	-	2.880		-	-----	-----
	Dwell Time	msec	-	307.198		-	≤ 400 msec	PASS
	Burst Ratio	%	-	76.8		-	-----	-----
Dwell Time	mSec	-	277.16		-	≤ 400 msec	PASS	

TEST PLOTS

Under 1GHz CH Mid



Report No.: TMWK2305001503KR

12. TEST RESULT FOR BLUETOOTH (CH0~CH78) (FOR 8DPSK)

12.1 FREQUENCY ERROR

TEST RESULT

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	----	----
Number of hopping channel	----	-	79	20	----	----
Reading Frequency	MHz	2402.014	2441.015	2480.015	----	----
Frequency Tolerance	ppm	5.828476	6.14502	6.048387	-50 ≤ x ≤ +50	PASS


TEST RESULT

CH Low



Report No.: TMWK2305001503KR

CH Mid



CH High



Report No.: TMWK2305001503KR

12.2 ANTENNA POWER

TEST RESULT

Measurement Frequency	MHz	2402	2441	2480	Limit	Result		
Channel Number	Ch.	0	39	78	-----	-----		
Number of hopping channel	-----	-	79	20	-	-----		
Transmission Output Power	Calculated result	mW/MHz	-	0.051	0.197	-	≤ 3 mW/MHz	-----
	Tolerance	%	-	0.00	0.00	-	$-80 \leq x \leq +20$	PASS
	Measured value	dBm	-	5.5518		-	-----	-----
	On Time	msec	-	2.890		-	-----	-----
	Dwell Time	msec	-	308.265		-	≤ 400 msec	PASS
Burst Ratio	%	-	77.1		-	-----	-----	

TEST PLOTS

CH Mid



Report No.: TMWK2305001503KR


12.3 UNWANTED EMISSION STRENGTH

TEST RESULT

Measurement Frequency		MHz	2402	2441	2480	Limit	Result
Channel Number		Ch.	0	39	78	----	----
Number of hopping channel		----	-	79	20	----	----
Unwanted Emission Strength	Under 2387MHz	μW/MHz	-	0.018750	-	≤2.5uW/MHz	PASS
		MHz	-	2313.30	-	----	----
	2387-2400MHz	μW/MHz	-	0.060954	-	≤25uW/MHz	PASS
		MHz	-	2399.05	-	----	----
	2483.5-2496.5MHz	μW/MHz	-	0.119124	-	≤25uW/MHz	PASS
		MHz	-	2483.56	-	----	----
	Over 2496.5MHz	μW/MHz	-	0.035075	-	≤2.5uW/MHz	PASS
		MHz	-	3845.50	-	----	----

TEST PLOTS

Under 2387MHz CH Mid




Report No.: TMWK2305001503KR

2387-2400MHz CH Mid




2483.5-2496.5MHz CH Mid



Report No.: TMWK2305001503KR

Over 2496.5MHz CH Mid



Report No.: TMWK2305001503KR

12.4 OCCUPIED BANDWIDTH –NORMAL (99%)


TEST RESULT

BT, 8DPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Occupied Bandwidth	MHz	-	78.192	19.967	≤83.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

12.5 SPREAD-SPECTRUM BANDWIDTH –NORMAL (90%)


TEST RESULT

BT, 8DPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Spread Bandwidth	MHz	-	71.001	18.198	≥ 0.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

12.6 OCCUPIED BANDWIDTH –AFH-(99%)


TEST RESULT

BT, 8DPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Occupied Bandwidth	MHz	-	78.192	19.967	≤83.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

12.7 SPREAD-SPECTRUM BANDWIDTH –AFH(90%)


TEST RESULT

BT, 8DPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result
Channel Number	Ch.	0	39	78	-----	-----
Number of hopping channel	-----	-	79	20	-----	-----
Spread Bandwidth	MHz	-	71.001	18.198	≥ 0.5 MHz	PASS

TEST PLOTS

Hopping



Report No.: TMWK2305001503KR

12.8 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER

TEST RESULT

BT, 8DPSK

Measurement Frequency	MHz	2402	2441	2480	Limit	Result	
Channel Number	Ch.	0	39	78	-----	-----	
Number of hopping channel	-----	-	79	20	-----	-----	
Secondarily Emitted Radio Wave Strength (RX Spurious)	Under 1GHz	nW	-	0.011508	-	≤ 4 nW	PASS
		MHz	-	106.00	-	-----	-----
	Over 1GHz	nW	-	0.091201	-	≤ 20 nW	PASS
		MHz	-	3250.00	-	-----	-----
Tested Circuit Insertion Loss for RX Spurious						1	

TEST PLOTS

Under 1GHz CH Mid



Report No.: TMWK2305001503KR

Over 1GHz CH Mid



Report No.: TMWK2305001503KR


12.9 DWELL TIME

TEST RESULT

Measurement Frequency	MHz	2402	2441	2480	Limit	Result		
Channel Number	Ch.	0	39	78	----	----		
Number of hopping channel	----	-	79	20	----	----		
Transmission Output Power	Calculated result	mW/MHz	-	0.051	0.197	-	≤ 3 mW/MHz	----
	Tolerance	%	-	0.00	0.00	-	$-80 \leq x \leq +20$	PASS
	Measured value	dBm	-	5.5518		-	----	----
	On Time	msec	-	2.890		-	----	----
	Dwell Time	msec	-	308.265		-	≤ 400 msec	PASS
	Burst Ratio	%	-	77.1		-	----	----
Dwell Time	mSec	-	276.61		-	≤ 400 msec	PASS	

TEST PLOTS

Under 1GHz CH Mid



Report No.: TMWK2305001503KR

13. TEST RESULT FOR BLE 1M (CH0~CH39)(FOR GFSK)


13.1 FREQUENCY ERROR

TEST RESULT

Measurement Frequency	MHz	2402	2442	2480	Result	NOTES
Channel Number	Ch.	0	20	39	-----	
Reading Frequency	MHz	2402.013	2442.014	2480.015	-----	
Frequency Tolerance	ppm	5.41216	5.73301	6.04839	PASS	


TEST PLOTS

CH Low




Report No.: TMWK2305001503KR

CH Mid



CH High



Report No.: TMWK2305001503KR


13.2 ANTENNA POWER

TEST RESULT

Measurement Frequency	MHz	2402	2442	2480	Result	NOTES
Channel Number	Ch.	0	20	39	-----	
RF Output Power	mW	6.235	6.331	6.218	PASS	
	dBm	7.9482	8.0145	7.9363		
RF Output Power Tolerance	%	-1.52	-0.01	-1.79	PASS	

TEST PLOTS

CH Low







Report No.: TMWK2305001503KR

Page 161 / 193
Rev. 00

CH Mid



CH High



Report No.: TMWK2305001503KR

13.3 UNWANTED EMISSION STRENGTH

TEST RESULT

Measurement Frequency		MHz	2402	2442	2480	Result	NOTES
Channel Number		Ch.	0	20	39	----	
Unwanted Emission Strength (TX1)	Under 2387MHz	μW/MHz	0.016558	0.019953	0.018535	PASS	
		dBm/MHz	-47.81	-47.00	-47.32		
		MHz	2314.10	2311.50	2135.90		----
	2387-2400MHz	μW/MHz	1.659587	0.013428	0.012162	PASS	
		dBm/MHz	-27.80	-48.72	-49.15		
		MHz	2400.00	2395.60	2399.77		----
	2483.5-2496.5MHz	μW/MHz	0.013459	0.012853	0.098628	PASS	
		dBm/MHz	-48.71	-48.91	-40.06		
		MHz	2485.83	2487.81	2484.40		----
	2496.5 - 12.5GHz	μW/MHz	0.029580	0.026363	0.027290	PASS	
		dBm/MHz	-45.29	-45.79	-45.64		
		MHz	3795.50	8550.50	3729.50		----

TEST PLOTS

Under 2387MHz CH Low



Report No.: TMWK2305001503KR

CH Mid



CH High




Report No.: TMWK2305001503KR


2387-2400MHz CH Low



CH Mid




CH High




Report No.: TMWK2305001503KR


2483.5-2496.5MHz CH Low



CH Mid



CH High



Report No.: TMWK2305001503KR

2496.5 - 12.5GHz CH Low



CH Mid



CH High



Report No.: TMWK2305001503KR


13.4 OCCUPIED BANDWIDTH (99%)

TEST RESULT

Measurement Frequency	MHz	2402	2442	2480	Result	NOTES
Channel Number	Ch.	0	20	39	-----	
Occupied Bandwidth	MHz	1.0343	1.0354	1.0342	PASS	


TEST PLOTS

CH Low



Report No.: TMWK2305001503KR

CH Mid



CH High



Report No.: TMWK2305001503KR


13.5 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER

TEST RESULT

Measurement Frequency		MHz	2402	2442	2480	Result	NOTES
Channel Number		Ch.	0	20	39	-----	
Secondarily Emitted Radio Wave Strength (RX Spurious) (RX1)	Under 1GHz	nW/MHz	0.0415	0.0547	0.0522	PASS	
		dBm/MHz	-73.82	-72.62	-72.82		
		MHz	105.90	106.00	106.00		-----
	1 - 12.5GHz	nW/MHz	0.0422	0.1706	0.3319	PASS	
		dBm/MHz	-73.75	-67.68	-64.79		
		MHz	3249.00	1945.00	2402.00		-----

TEST PLOTS

Under 1GHz CH Low



CH Mid



CH High



Report No.: TMWK2305001503KR

1 - 12.5GHz CH Low




CH Mid



Report No.: TMWK2305001503KR

CH High



Report No.: TMWK2305001503KR

14. TEST RESULT FOR BLE 2M (CH0~CH39)(FOR GFSK)


14.1 FREQUENCY ERROR

TEST RESULT

Measurement Frequency	MHz	2402	2442	2480	Result	NOTES
Channel Number	Ch.	0	20	39	-----	
Reading Frequency	MHz	2402.013	2442.014	2480.015	-----	
Frequency Tolerance	ppm	5.41216	5.73301	6.04839	PASS	


TEST PLOTS

CH Low



Report No.: TMWK2305001503KR

CH Mid



CH High



Report No.: TMWK2305001503KR


14.2 ANTENNA POWER

TEST RESULT


Measurement Frequency	MHz	2402	2442	2480	Result	NOTES
Channel Number	Ch.	0	20	39	----	
RF Output Power	mW	6.007	6.040	5.934	PASS	
	dBm	7.7867	7.8103	7.7334		
RF Output Power Tolerance	%	-0.54	0.01	-1.75	PASS	

TEST PLOTS


CH Low



CH Mid



CH High



Report No.: TMWK2305001503KR


14.3 UNWANTED EMISSION STRENGTH

TEST RESULT

Measurement Frequency		MHz	2402	2442	2480	Result	NOTES
Channel Number		Ch.	0	20	39	-----	
Unwanted Emission Strength (TX1)	Under 2387MHz	μW/MHz	0.020797	0.018664	0.020749	PASS	
		dBm/MHz	-46.82	-47.29	-46.83		
		MHz	2385.50	2250.30	2360.90		-----
	2387-2400MHz	μW/MHz	4.027170	0.012764	0.013868	PASS	
		dBm/MHz	-23.95	-48.94	-48.58		
		MHz	2400.00	2398.93	2397.80		-----
	2483.5-2496.5MHz	μW/MHz	0.014622	0.014421	0.217771	PASS	
		dBm/MHz	-48.35	-48.41	-36.62		
		MHz	2489.45	2489.32	2483.51		-----
	2496.5 - 12.5GHz	μW/MHz	0.036141	0.029040	0.024774	PASS	
		dBm/MHz	-44.42	-45.37	-46.06		
		MHz	3813.00	3824.50	5119.50		-----

TEST PLOTS

Under 2387MHz CH Low



Report No.: TMWK2305001503KR

CH Mid




CH High




Report No.: TMWK2305001503KR

2387-2400MHz CH Low



CH Low (Sample)




Report No.: TMWK2305001503KR

CH Mid



CH High




Report No.: TMWK2305001503KR


2483.5-2496.5MHz CH Low



CH Mid




CH High



Report No.: TMWK2305001503KR

2496.5 - 12.5GHz CH Low



CH Mid



CH High



Report No.: TMWK2305001503KR

14.4 OCCUPIED BANDWIDTH (99%)

TEST RESULT

Measurement Frequency	MHz	2402	2442	2480	Result	NOTES
Channel Number	Ch.	0	20	39	-----	
Occupied Bandwidth	MHz	2.0458	2.0460	2.0475	PASS	

TEST PLOTS

CH Low



CH Mid



CH High



Report No.: TMWK2305001503KR

14.5 LIMITATION OF COLLATERAL EMISSIONS OF RECEIVER

TEST RESULT

Measurement Frequency		MHz	2402	2442	2480	Result	NOTES
Channel Number		Ch.	0	20	39	-----	
Secondarily Emitted Radio Wave Strength (RX Spurious) (RX1)	Under 1GHz	nW/MHz	0.0376	0.0364	0.0410	PASS	
		dBm/MHz	-74.25	-74.39	-73.87		
		MHz	106.00	106.00	106.00		-----
	1 - 12.5GHz	nW/MHz	0.3119	0.3556	0.1114	PASS	
		dBm/MHz	-65.06	-64.49	-69.53		
		MHz	2480.00	1944.00	1945.00		-----


TEST PLOTS

Under 1GHz CH Low



Report No.: TMWK2305001503KR

CH Mid




CH High




Report No.: TMWK2305001503KR

1 - 12.5GHz CH Low




CH Mid




Report No.: TMWK2305001503KR

CH High



15. Interference Prevention Function



Interference Prevention Function	By identifying the characteristics of the modulation scheme of the received radio waves and others, shall be able to identify the reflected waves of the radio waves which local station transmitted and the radio waves transmitted by other radio stations.
MAC address	Bluetooth: 00-1F-7B-4A-00-01 WIFI: 00:1f:7b:1e:30:25
Result	Pass

- End of Test Report -

APPENDIX A - PHOTOGRAPHS OF TEST SETUP

